

## tender file

### **Universal-Filter 3 XL external, suitable for pedestrian loading**

Rainwater Universal-Filter 3 XL external, suitable for pedestrian loading, for installation into the ground. High efficiency 100%, easy cleaning due to a smooth sieve structure. Continuously variable installation depth of 703 mm to 1,270 mm (27.7" to 50") using the telescopic dome shaft. Sealed up to the top edge of the ground due to profile seal. Connection DN 160 / DN 200 (6" / 8" pipe).

- Cage material: polyethylene (PE)
- Filter material: stainless steel
- Mesh width: 0.75 mm (0.03")
- Efficiency: 100%
- Length: 1,140 mm (44.9")
- Width: 690 mm (27.2")
- Height: 870 mm (34.3") – to be cut on demand

Can manage roof areas up to 750 m<sup>2</sup> (8,072.9 ft<sup>2</sup>) – DN 160 (6" pipe) / 1,200 m<sup>2</sup> (12,916.7 ft<sup>2</sup>) – DN 200 (8" pipe). Offset high between inlet and outlet: 229 mm (9").

### **Product: GRAF Universal-Filter 3 external, suitable for pedestrian loading**

### **Universal-Filter 3 XL external, suitable for vehicle loading**

Rainwater Universal-Filter 3 XL external with cast iron cover class B, suitable for vehicle loading class B 125, for installation into the ground. High efficiency 100%, easy cleaning due to a smooth sieve structure. Continuously variable installation depth of 703 mm to 1,270 mm (27.7" to 50") using the telescopic dome shaft. Sealed up to the top edge of the ground due to profile seal. Connection DN 160 / DN 200 (6" / 8" pipe).

- Cage material: polyethylene (PE)
- Filter material: stainless steel
- Mesh width: 0.75 mm (0.03")
- Efficiency: 100%
- Length: 1,140 mm (44.9")
- Width: 690 mm (27.2")
- Height: 870 mm (34.3") – to be cut on demand

Can manage roof areas up to 750 m<sup>2</sup> (8,072.9 ft<sup>2</sup>) – DN 160 (6" pipe) / 1,200 m<sup>2</sup> (12,916.7 ft<sup>2</sup>) – DN 200 (8" pipe). Offset high between inlet and outlet: 229 mm (9").

### **Product: GRAF Universal-Filter 3 XL external, suitable for vehicle loading**