

## tender file

### **Cesspool Carat S for storage of silage and liquid manure**

Cesspool Carat S for storage of silage and liquid manure. Made from Duralen®, a high-quality material, 100% recyclable with 8 connection possibilities DN 100/150 (4"/6" pipe) – 5 prepared with lip seal DN 100 (4" pipe). Large dome shaft (360° turnable) for easy access according to DIN 1989. Access opening Ø 800/600 mm (31,5"/23,6"), H= 610 mm (24"). 15 years warranty from manufacturer. Cesspool incl. telescopic dome shaft LKW suitable for standard concrete rings and BEGU covers (provided by customers). Reservoir certified for stability and tightness according to DIN EN 12566-3.

- Tank volume: ..... liter (US gal.)

### **Product: GRAF Cesspool Carat S for silage and liquid manure**

### **Telescopic dome shaft with PP lid, suitable for pedestrian loading**

Telescopic dome shaft with PP lid, suitable for pedestrian loading allows height adjustment to ensure flush level fitting with surrounding ground surface between 650 and 900 mm (25.6" and 35.4"). Including EPDM seal and EPDM clamping profile, sealed up to the top edge of ground. Flat design for a flushed closure, can be tilted by max. 5°. Cover closing by a stainless steel screw with an M 10 thread and anti-twist protection.

- Short-term load: max. 150 kg (330,7 lbs)
- Long-term load: max. 50 kg (110,2 lbs)

### **Product: GRAF Telescopic dome shaft with PP lid, suitable for pedestrian loading**

### **Extension**

An earth covering of >900 mm (35.4") can be implemented using the extension and the telescopic dome shaft.

H = 500 mm (19.7"), Ø 700 mm (27.6"). Material: polyethylene (PE), 100% recyclable.

### **Product: GRAF Extension**

### **Telescopic dome shaft with cast iron lid, class B**

Telescopic dome shaft with class B 125 cast iron cover, suitable for vehicle loading allows the infinitely adjustment to ground situations between 650 and 900 mm (25.6" and 35.4"). Flat design for a flushed closure, can be tilted by max. 5°. Suitable for vehicle loading class B125. Sealed up to the top edge of ground due to EPDM seal and EPDM clamping profile.

Weight:

- Telescopic dome shaft approx. 6 kg (13.2 lds)
- Lid approx. 60 kg (132.3 lds)

### **Product: GRAF Telescopic dome shaft with cast iron lid, suitable for vehicle loading**



tender file

**Telescopic dome shaft LKW, suitable for vehicle loading**

Telescopic dome shaft LKW for standard concrete rings/BEGU-covers allows height adjustment to ensure flush level fitting with surrounding ground surface between 650 and 900 mm (25.6" and 35.4"). For standard concrete rings and BEGU-covers (provided by customer). Sealed up to the top edge of telescopic dome shaft due to EPDM seal and EPDM clamping profile, can be tilted by max. 5°. For tarred surfaces.

**Product: GRAF Telescopic dome shaft LKW, suitable for vehicle loading**