

tender file

KSB-Superinox 15/4

KSB-Superinox 15/4 including Controlmatic pressure and flow monitor. Very quiet-running automatic domestic water system for detached homes and smaller apartment blocks. With 24-hour service hotline and 24-hour on-site repair service throughout Germany. With integrated dry running protection and backflow preventer. Lifelong motor lubrication for reliable operation.

Technical data:

- Max. motor output: 0.66 KW
- Max. delivery height: 35 m
- Max. pressure: 3.5 bar
- Max. delivery rate: 3600 l/h
- Max. suction lift: 8 m
- Suction length connection: 18 m
- Suction side connection: 1" inside thread
- Pressure side: 1" outside thread (on pressure and flow monitor)

Product: KSB-Superinox 15/4

KSB-Superinox 25/4

KSB-Superinox 15/4 including Controlmatic pressure and flow monitor. Very quiet-running automatic domestic water system for detached homes and smaller apartment blocks. With 24-hour service hotline and 24-hour on-site repair service throughout Germany. With integrated dry running protection and backflow preventer. Lifelong motor lubrication for reliable operation.

Technical data:

- Max. motor output: 0.8 KW
- Max. delivery height: 43 m
- Max. pressure: 4.2 bar
- Max. delivery rate: 4200 l/h
- Max. suction lift: 8 m
- Suction length: 18 m
- Suction side connection: 1" inside thread
- Pressure side: 1" outside thread (on pressure and flow monitor)

Product: KSB-Superinox 25/4

Centrifugal 4/1000

Centrifugal 4/1000 Self-priming automatic domestic water system for domestic supply including Pump control pressure and flow monitor. Long service life thanks to double-insulated rotor discs; metal parts do not come into contact with the conveyed medium. With cable, plug and dry running protection as standard.

Technical data:

- Max. motor output: 0.8 KW
- Max. delivery height: 48 m

tender file

- Max. pressure: 4.8 bar
- Max. delivery rate: 4800 l/h
- Max. suction lift: 8 m
- Suction length: 15 m
- Suction side connection: 1" inside thread
- Pressure side connection: 1" inside thread (on pressure and flow monitor)

Product: GRAF Centrifugal 4/1000

Jet 700 garden pump

Self-priming jet pump 700 for watering the garden. Long service life thanks to double-insulated rotor discs; metal parts do not come into contact with the conveyed medium. With cable, plug and splash-protected switch as standard.

Technical data:

- Motor output: 0.7 KW
- Max. delivery height: 40 m
- Max. pressure: 4.0 bar
- Max. delivery rate: 3000 l/h
- Max. suction lift: 8 m
- Suction length connection: 15 m
- Suction side connection: 1" outer thread
- Pressure side: 1" outer thread

Product: GRAF Jet 700 garden pump

Integra stainless steel submersible and suction pump

Integra stainless steel submersible and suction pump including floating water extraction unit and integrated pressure and flow monitor for watering the garden. Long service life: all metal parts that come into contact with the conveyed medium are made of high-quality stainless steel. Includes 10 m connection cable, plug and dry running protection.

Technical data:

- Motor output: 0.6 KW
- Max. delivery height: 40 m
- Max. pressure: 4.0 bar
- Max. delivery rate: 3000 l/h
- Max. suction lift: 8 m
- Max. suction length: 12 m
- Max. submersion depth: 10 m
- Suction side connection: 1" inside thread
- Pressure side connection: 1¼" inside thread

Product: GRAF Integra stainless steel submersible and suction pump

tender file

Submersible pump 300 A

Submersible pump 300 A with floating switch control and 10 m connection cable for small gardens and pond systems. Includes dry running protection.

Technical data:

- Motor output: 0.3 KW
- Max. delivery height: 7 m
- Max. pressure: 0.7 bar
- Max. delivery rate: 7200 l/h
- Max. submersion depth: 3 m
- Pressure side connection: 1¼" inside thread

Product: GRAF Submersible pump 300 A

Submersible pressure pump 1000 A

Submersible pressure pump 1000 A with floating switch control and 15 m connection cable for detached homes and smaller apartment blocks. High capacity (6000 l/h), therefore also suitable for watering larger gardens. Includes dry running protection.

Technical data:

- Motor output: 0.9 KW
- Max. delivery height: 36 m
- Max. pressure: 3.6 bar
- Max. delivery rate: 6000 l/h
- Max. submersion depth: 8 m
- Pressure side connection: 1" inside thread

Product: GRAF Submersible pressure pump 1000 A

Submersible pressure pump 1000 E

Submersible pressure pump 1000 E with integrated pressure and flow monitor and 15 m connection cable for detached homes and smaller apartment blocks. High capacity (5600 l/h), therefore also suitable for watering larger gardens. Automatic control – little installation work required. Includes dry running protection.

Technical data:

- Max. motor output: 0.9 KW
- Max. delivery height: 36 m
- Max. pressure: 3.6 bar
- Max. delivery rate: 5600 l/h
- Max. submersion depth: 8 m
- Connection: 1" inside thread

Product: GRAF Submersible pressure pump 1000 E



tender file

Reversible flow filter for fine filtering

Reversible flow filter for fine filtering of rainwater downstream of the pump, ideal when a washing machine is to be connected. Reliably holds back even the finest dirt particles measuring over 0.1 mm. Filter surface easy to clean without removing or replacing the filter. DVGW-tested design.

- Connections: 25mm (1")

Product: GRAF Reversible flow filter for fine filtering

Controlmatic automatic pump switch unit

Controlmatic automatic pump switch unit with dry running protection and pressure gauge Maintains constant pipe pressure. Fully wired with connector plug.

With integrated filter cleaning unit as standard.

- Activation pressure: 1.5 - 2.6 bar (individually adjustable)
- Protection category: IP 44
- Connections: 1" outer thread

Product: GRAF Controlmatic automatic pump switch unit