

tender file

EcoBloc Inspect flex

The EcoBloc Inspect flex can be used for detention, retention and infiltration of rainwater or surface water and must always be fitted and installed on the EcoBloc Inspect baseplates. The EcoBloc Inspect elements should be connected together using Eco connectors. Multiple layers can be laid by using multiple EcoBloc Inspect flex elements without any other accessories. Maximum number of layers 14 (vehicle load) or 13 (HGV60/HS-25 load). Inspection and cleaning by self-propelling camera cart or probes with connection of DN 200 (8" pipe) Inspection entries. Open interior structure ensures good visibility and ease of movement as well as multidimensional through flow. Long-term load-bearing capacity up to HGV60 load (HS-25) verified.

Technical data:

Dimensions (LxWxH): 800 x 800 x 320 mm (31.44" x 31.44" x 12.6")

Weight: approx. 8 kg (17.6 lbs)

Material: Polypropylene PP (100 % recyclable)

Colour: Grey

Volume: 205 litres / 195 litres (54 US gal. net) / (51.5 US gal. net)

Reservoir coefficient: 95 %

Connections: 4 x DN 200/160/110 + 4 x DN 110 (4 x 8"/6"/4" + 4 x 4")

Note:

The EcoBloc Inspect should be laid on a geotextile or membrane which in turn is laid on a blinding which has been smoothed flat. Installation of the system should be carried out following the manufacturer's instructions.

Product: EcoBloc Inspect flex

Accessory

EcoBloc Inspect baseplate

Baseplate for laying EcoBloc Inspect flex 205 infiltration elements. Baseplates should be laid to give sufficient coverage by positioning with Eco connectors – see separate item. Long-term load-bearing capacity up to HGV60 (HS-25) load verified.

Technical data:

Dimensions (L x W x H): 800 x 800 x 40 mm (31.44" x 31.44" x 1.57")

Weight: 4 kg (8.8 lbs.)

Material: Polypropylene PP (100 % recyclable)

Colour: Grey

Volume: 25 litres (6.6 US-gal.)

Note:

Each EcoBloc Inspect baseplate should be laid on a geotextile or membrane – see GRAF Tex geotextile – which in turn is laid on an excavation which has been smoothed flat – again see excavation instructions. Installation of the system should be carried out following the manufacturer's instructions and strictly adhered to.

Product: GRAF EcoBloc Inspect baseplate

tender file

EcoBloc Inspect end plate - Eco end plate set

EcoBloc Inspect end plates are fitted at the end of every row of GRAF EcoBloc Inspect flex 205. They include connection surfaces of different pipe sizes.

Technical data:

Set consists of two end plates

Dimensions (LxWxH): 742 x 660 x 54 mm (29.2" x 25.98" x 2.1")

Material: Polypropylene PP (100 % recyclable)

Colour: Grey

One Eco end plate is needed for each EcoBloc Inspect flex 205 face plate (at end of row only).

Connections: 2 x DN 200/160/110 (2 x 8"/6"/4") per plate

Product: GRAF EcoBloc Inspect end plate - Eco end plate set

Eco connectors

Eco Connectors are used to secure individual EcoBloc units together to form the larger EcoBloc assembly. One connector is required for each contact side of the EcoBloc.

Technical data:

Dimensions (LxWxH): 68 x 26 x 38 mm (2.67" x 1.02" x 1.5")

Material: Polypropylene PP

Product: GRAF Eco connectors

GRAF-Tex geotextile

Graf-Tex geotextile (8 ounce, non-woven geo-textile fabric), 100 % polypropylene filter membrane, mechanically needle-punched to form continuous filament. Rot-proof material between soil and infiltration system prevents infiltration layers from silting up. The Graf-Tex geotextile ensures long lifetime, consistent infiltration and high permeability.

Technical data:

Opening width: 100 µm

Water permeability coefficient kv (s = 20 kPa): 1.0×10^{-3} m/s

Tensile strength (lengthwise / crosswise): 15 kN/m / 15 kN/m

Punch push-through force (x-s): 2.0 kN

Weight: 200 g/m²

Robustness class: 3

Roll material: Roll width 5 m (196.9")

Product: GRAF-Tex geotextile

tender file

Deaeration end DN 110 (4")

Deaeration end DN 110 (4") should always be installed for attenuation/infiltration systems in the event of heavy inflow of rain/surface water or undersized house venting installation.

Technical data:

DN 110 (4")

Colour: Black

Rodent guard

Can be extended with standard DN 110 (4")

Product: GRAF Deaeration end DN 110 (4")

Deaeration cover DN 160/200 (6"/8")

Deaeration cover DN 160/200 (6"/8") should always be installed for attenuation/infiltration systems in the event of heavy inflow of rain/surface water or undersized house venting installation.

Technical data:

DN 160/200 (6"/8")

Colour: Black

Can be extended with standard DN 160/200 pipes (6"/8")

Product: GRAF Deaeration cover DN 160/200 (6"/8")

Additional items without material / service from Otto GRAF GmbH

Excavation for EcoBloc Inspect system

8 – 10 cm (3.15" – 3.94") thick layer of gravel 8mm/16mm (0.03"/0.06").

Compressed with lightweight machine as horizontal and level plane to lay geotextile and EcoBloc Inspect elements – see separate items –.

Backfill for EcoBloc Inspect System

Gravel of size 20mm/40mm (0.79"/1.57") for side and vertical filling of EcoBloc Inspect System.

If EcoBloc Inspect are to be filled in layers, observe maximum fill height of around 300 mm (0.98') and compress in layers in accordance with manufacturer's instructions.