



Tender file

Platin XL / XXL infiltration tank

Platin XL / XXL infiltration tank (10,000 to 65,000 litres) for decentralised infiltration and retention of rainwater from sealed surfaces.

Truck passable up to SLW 30 – with load distribution plate to be provided on site and corresponding cover.

Up to 15,000 litres seamlessly manufactured from one piece.

Made of high-quality polyethylene (PE); 100% recyclable.

Even infiltration flow through perforated drainage hose.

Volume tank easy to inspect and clean.

Numerous connection options DN 100/150/200. Larger connection pieces up to DN 300 on request.

Dome opening with rotated stainless steel ring - patented - for extreme stability as well as highest fitting accuracy and assembly safety.

Large entrance dome (360° rotatable) according to DIN 1989.

Access opening Ø 800/650 mm, H = 610 mm. Optional production with second tank dome possible.

Sealed up to the top edge of the terrain in connection with telescopic dome shaft and profile seal.

Tank casing with round grain gravel (max. grain size 8/16). Note the details in our instructions.

Up to 40,000 litres volume can be transported without special transport.

15 years manufacturer warranty.

Tank volume:..... litres

Length: from 4900 mm

Width: 2250 mm

Height: 1250 mm

Weight: from 460 kg

Fabrikat: GRAF Platin XL / XXL infiltration tank