

Tender file

Platin XXL firefighting water tank

Platin XXL firefighting water tank (20,000 to 65,000 litres), similar to DIN 14230

Truck passable up to SLW 30 – with load distribution plate to be provided on site and corresponding cover.
Made of high-quality polyethylene (PE), 100% recyclable.

Incl. telescopic dome shaft truck for on-site cover according to DIN 3223.

V2A Suction pipe with flange DN 125, incl. extinguishing water suction connection with sounding pipe (RAL 3000)

A-fixed coupling with metallic sealing surface made of aluminium according to DIN 14319,

Blank coupling according to DIN 14313 including chain,

V2A suction basket and PE anti-vortex plate Ø 600 mm,

V2A Ventilation chimney with insect-proof stainless steel sieve DN 100,

V2A holder for information sign "Extinguishing water tapping point" with post,

ALU access ladder and mounting kit.

Numerous connection options DN 100/150/200. Larger connection pieces up to DN 300 on request.

Dome opening with rotated stainless steel ring - patented - for extreme stability as well as highest fitting accuracy and installation safety.

Large entrance dome (360° rotatable) according to DIN 1989.

Access opening Ø 800/650 mm, H = 610 mm. Optional production with second tank dome possible.

Sealed up to the top edge of the terrain in connection with telescopic dome shaft and profile seal.

Up to 40,000 litres volume can be transported without special transport.

15 years manufacturer warranty.

Tank volume: litres

Useful volume: litres

Length: from 9405 mm

Width: 2250 mm

Height: 1250 mm

Weight: from 890 kg

Fabricate: GRAF Platin XXL firefighting water tank

Tender file

Platin XXL firefighting extension water tank

Platin XXL firefighting extension water tank (20,000 to 65,000 litres), similar to DIN 14230

Truck passable up to SLW 30 – with load distribution plate to be provided on site and corresponding cover.
Made of high-quality polyethylene (PE), 100% recyclable.

Incl. telescopic dome shaft “truck” for on-site cover according to DIN 3223,
V2A Ventilation chimney with insect-proof stainless steel sieve DN 100,
ALU access ladder and mounting kit.
and other accessories.

Numerous connection options DN 100/150/200. Larger connection pieces up to DN 300 on request.

Dome opening with rotated stainless steel ring - patented - for extreme stability as well as highest fitting accuracy and installation safety.

Large entrance dome (360° rotatable) according to DIN 1989.

Access opening Ø 800/650 mm, H = 610 mm. Optional production with second tank dome possible.
Sealed up to the top edge of the terrain in connection with telescopic dome shaft and profile seal.

Up to 40,000 litres volume can be transported without special transport.

15 years manufacturer warranty.

Tank volume: litres

Useful water volume: litres

Length: from 9405 mm

Width: 2250 mm

Height: 1250 mm

Weight: from 890 kg

Fabricate: Platin XXL firefighting extension water tank