

tender file

Universal-Industrial Filter 3 external, suitable for pedestrian loading

Rainwater Universal-Industrial Filter 3 external, suitable for pedestrian loading, for installation into the ground. High efficiency 100%, easy cleaning due to a smooth sieve structure. Continuously variable installation depth of 705 mm to 1,270 mm (27.7" to 50") using the telescopic dome shaft. Sealed up to the top edge of the ground due to profile seal. Connection DN 160 / DN 200 (6" / 8" pipe).

- Cage material: polyethylene (PE)
- Filter material: stainless steel
- Mesh width: 0.75 mm (0.03")
- Efficiency: 100%
- Length: 1,140 mm (44.9")
- Width: 690 mm (27.2")
- Height: 870 mm (34.3") – to be cut on demand

Can manage roof areas up to 750 m² (8,072.9 ft²) – DN 160 (6" pipe) / 1,200 m² (12,916.7 ft²) – DN 200 (8" pipe). Offset high between inlet and outlet: 229 mm (9").

Product: GRAF Universal-Filter 3 external, suitable for pedestrian loading

Universal-Industrial Filter 3 external, suitable for vehicle loading

Rainwater Universal-Industrial Filter 3 external with Telescopic dome shaft 600 PKW suitable for vehicle loading up to 3,5 t inclusive childproof plastic lid for installation in the ground. High efficiency 100%, easy cleaning due to a smooth sieve structure. Continuously variable installation depth of 705 mm to 1,270 mm (27.7" to 50") using the telescopic dome shaft. Sealed up to the top edge of the ground due to profile seal. Connection DN 160 / DN 200 (6" / 8" pipe).

- Cage material: polyethylene (PE)
- Filter material: stainless steel
- Mesh width: 0.75 mm (0.03")
- Efficiency: 100%
- Length: 1,140 mm (44.9")
- Width: 690 mm (27.2")
- Height: 870 mm (34.3") – to be cut on demand

Can manage roof areas up to 750 m² (8,072.9 ft²) – DN 160 (6" pipe) / 1,200 m² (12,916.7 ft²) – DN 200 (8" pipe). Offset high between inlet and outlet: 229 mm (9").

Product: GRAF Universal-Filter 3 external, suitable for vehicle loading